



HEAVY DUTY TRUCK/BUS TYRES





SUPERLUG

Features	Benefits
<ul style="list-style-type: none"> • Special tread compound • Increased number of lugs • Special design with scoops at shoulder • Extra strong casing 	<ul style="list-style-type: none"> • Excellent mileage • Improved traction • Faster heat dissipation and cooler running • Better safety and more retreads

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
10.00-22	12	7.5	285	1130	20.5	2650@6.00	2300@5.30	529	22RR	TR 78A
10.00-22	14	7.5	285	1130	20.5	3000@7.00	2575@6.30	529	22RR	TR 78A
11.00-22	16	8.0	290	1160	21.5	3525@8.15	3090@7.45	538	22RR	TR 78A
11-22.5	12	8.25	280	1085	20.5	2465@6.00	2160@5.30	511	-	Tubeless
11-22.5	16	8.25	280	1085	20.5	3005@8.10	2635@7.40	511	-	Tubeless
11-24.5	12	8.25	285	1145	20.5	2625@6.00	2305@5.30	540	-	Tubeless
11-24.5	16	8.25	285	1145	20.5	3195@8.10	2805@7.40	540	-	Tubeless
12.00-24	18	8.5	310	1245	22.0	4250@8.15	3725@7.45	583	24R	TR 78A



SUPERLUG 78

Features	Benefits
<ul style="list-style-type: none"> • Unique tread compound • More lugs • Special design with scoops at shoulder • Extra strong casing 	<ul style="list-style-type: none"> • Excellent mileage • Better road grip • More circulation of air and faster heat dissipation • Better safety and more retreads

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.50-20	12	6.0	225	960	18.0	1775@7.40	1555@6.70	448	20M	TR 177A
8.25-20	10	6.5	250	1015	19.0	1840@6.0	1615@5.3	477	20M	TR 175A
8.25-20	12	6.5	250	1005	19.0	2040@7.0	1790@6.3	475	20M	TR 175A
8.25-20	14	6.5	240	995	19.0	2230@8.15	1000@7.40	472	20M	TR 175A
9.00-20	14	7.0	260	1040	20.4	2570@7.65	2255@7.15	490	20N	TR 175A
9.00-20	16	7.0	260	1040	20.4	2650@8.15	2325@7.40	490	20N	TR 175A
10.00-20	16	7.5	275	1070	21.6	3000@8.15	2630@7.40	501	20N	TR 78A
11.00-20	16	8.0	295	1100	21.6	3265@8.10	2865@7.40	520	20RR	TR 78A
12.00-20	16	8.5	305	1135	21.6	3510@7.40	3080@6.70	528	20RR	TR 78A
12.00-20	18	8.5	305	1135	21.6	3725@8.10	3265@7.40	528	20RR	TR 78A

HEAVY DUTY TRUCK/BUS TYRES



NULUG



Features	Benefits
<ul style="list-style-type: none"> • Special transverse tread Pattern • Strong casing 	<ul style="list-style-type: none"> • Reduces stone trapping • Good traction • Durable

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
12.00-24	18	8.5	305	1240	20.5	4250@8.15	3728@7.45	578	24RR	TR 78A
12.00-20	18	8.5	300	1105	17.0	3725@8.10	3265@7.40	512	20RR	TR 78A

M - 77



Features	Benefits
<ul style="list-style-type: none"> • Rib lug tread pattern • Open & aggressive Tread design • Premium tread compound 	<ul style="list-style-type: none"> • All wheel fitment • Excellent traction • Enhanced mileage & Cut resistance

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
8.25-20	14	6.5	240	1000	19.0	2230@8.15	1960@7.40	472	20M	TR 175A
9.00-20	14	7.0	265	1050	21.4	2570@7.35	2255@7.15	490	20N	TR 175A
9.00-20	16	7.0	275	1060	21.5	2650@8.15	2325@7.4	496	20N	TR 175A
10.00-20	16	7.5	270	1070	21.6	3000@7.85	2630@7.40	504	20N	TR 78A
11.00-20	16	8.0	295	1100	21.6	3265@8.10	2865@7.40	520	20RR	TR 78A
12.00-20	18	8.5	315	1170	21.6	3725@8.10	3265@7.40	528	20RR	TR 78A
12.00-24	18	8.5	310	1245	22.0	4250@8.15	3728@7.45	583	24RR	TR 78A



SUPER LUG 50

Features	Benefits
<ul style="list-style-type: none"> • Premium Tread Compound • Unique tread compound • More lugs • Special design with scoops at shoulder • Extra strong casing 	<ul style="list-style-type: none"> • Excellent mileage • Excellent mileage • Better road grip • More circulation of air and faster heat dissipation • Better safety and more retreads

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
11.00-20	16	8.0	285	1085	22.5	3265@8.00	2855@7.35	503	20N	TR 78A

SUPER LUG 999 EXTRA



Features	Benefits
<ul style="list-style-type: none"> • Premium Tread Compound • More lugs • Special design with scoops at shoulder • strong casing 	<ul style="list-style-type: none"> • Excellent mileage • Better road grip • More circulation of air and faster heat dissipation • Better safety

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
8.25-20	14	6.5	235	995	21.5	2240@8.00	2000@7.35	472	20N	TR 175A
9.00-20	16	7.0	265	1050	23.5	2650@8.10	2325@7.40	496	20N	TR 78A
11.00-20	18	8.0	285	1085	23.5	3355@8.40	2945@7.75	506	20RR	TR 78A
12.00-20	18	8.5	310	1150	24.0	3750@8.00	3350@7.35	537	20RR	TR 78A



SUPER LUG EX



Features	Benefits
<ul style="list-style-type: none"> • Special tread compound • Increased number of lugs • Special design with scoops at shoulder • Extra strong casing 	<ul style="list-style-type: none"> • Excellent mileage • Improved traction • Faster heat dissipation and cooler running • Better safety and more retreads

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
9.00-20	16	7.0	260	1040	20.4	2650@8.10	2325@7.40	490	20N	TR 175A
10.00-20	16	7.5	275	1070	21.6	3000@8.00	2650@7.35	501	20N	TR 78A
11.00-20	16	8.0	295	1110	21.6	3265@8.00	2855@7.35	520	20RR	TR 78A
11.00-20	18	8.0	295	1110	21.6	3335@8.40	2945@7.75	520	20RR	TR 78A
12.00-20	18	8.5	305	1135	21.6	3750@8.00	3350@7.35	528	20RR	TR 78A

SUPER LUG EXTRA



Features	Benefits
<ul style="list-style-type: none"> • Cut Resistant Tread Compound • Unique tread compound • More lugs • Special design with scoops at shoulder • Extra strong casing 	<ul style="list-style-type: none"> • Excellent Protection against Tread Damage on Bad Roads • Excellent mileage • Better road grip • More circulation of air and faster heat dissipation • Better safety and more retreads

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
10.00-20	16	7.5	280	1075	23.0	3000@8.00	2650@7.35	505	20N	TR 78A

HEAVY DUTY TRUCK/BUS TYRES



MUSCLE LUG

Features	Benefits
<ul style="list-style-type: none"> • Special transverse tread pattern • Extra Strong casing • Optimised Weight and cost effective design 	<ul style="list-style-type: none"> • Reduces stone trapping • Better Safety--- • Good traction • Durable • Cost Effective

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
9.00-20	16	7.0	260	1035	16.5	2650@8.15	2325@7.40	482	20N	TR 175A
10.00-20	16	7.5	275	1055	17.0	3000@8.15	2630@7.40	492	20N	TR 78A
11.00-20	16	8.0	290	1093	16.5	3265@8.10	2865@7.40	507	20RR	TR 78A
12.00-20	18	8.5	305	1125	18.5	3725@8.10	3265@7.40	524	20RR	TR 78A



MUSCLE RIB

Features	Benefits
<ul style="list-style-type: none"> • Special transverse tread pattern • Extra Strong casing • Optimised Weight and cost effective design 	<ul style="list-style-type: none"> • Reduces stone trapping • Better Safety • More retreads • Good traction • Durable • Cost Effective

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
9.00-20	14	7.0	260	1025	14.0	2650@8.15	2325@7.40	479	20N	TR 175A
10.00-20	16	7.5	275	1053	14.0	3000@8.15	2630@7.40	493	20N	TR 78A
11.00-20	16	8.0	290	1080	14.5	3265@8.10	2865@7.40	500	20RR	TR 78A
12.00-20	18	8.5	312	1125	15.5	3725@8.10	3265@7.40	522	20RR	TR 78A

HEAVY DUTY TRUCK/BUS TYRES



SUPERMILER



Features	Benefits
<ul style="list-style-type: none"> • Traditional five rib design • Rugged all nylon carcass • Unique fan like rounded shoulder design • Premium tread compound 	<ul style="list-style-type: none"> • Dependable mileage and traction • Excellent strength and retreadability • Enhanced air circulation for cooling • Superior mileage

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
7.50-20	12	6.0	225	955	13.3	1775@7.40	1555@6.70	448	20M	TR 177A
8.25-20	12	6.5	245	990	14.5	2040@7.0	1790@6.3	467	20M	TR 175A
8.25-20	14	6.5	240	980	14.2	2230@8.15	1960@7.40	472	20M	TR 175A
9.00-20	14	7.0	260	1035	15.2	2570@7.65	2255@7.15	490	20N	TR 175A
9.00-20	16	7.0	260	1045	17.5	2650@8.10	2325@7.40	495	20N	TR 175A
10.00-20 SED	16	7.5	275	1063	18.0	3000@8.15	2630@7.40	500	20N	TR 78A

SUPER TRAILER



Features	Benefits
<ul style="list-style-type: none"> • Unique rib tread pattern for free rolling • Special tread compound 	<ul style="list-style-type: none"> • Good road grip • Heat dissipation due to circulation of air between voids • Crack resistant

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
10.00-20	14	7.5	280	1055	9.5	2740@7.00	2405@6.30	492	20 N	TR 78A

HEAVY DUTY TRUCK/BUS TYRES



MILER



Features	Benefits
<ul style="list-style-type: none"> • Unique rib tread pattern For free rolling 	<ul style="list-style-type: none"> • Good mileage • Dependable road grip

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
9.00-20	14	7.0	260	1020	15.5	2570@7.65	2255@7.15	479	20N	TR 175A
10.00-20	14	7.5	280	1065	13.5	2740@7.00	2405@6.30	498	20N	TR 78A

MILER



Features	Benefits
<ul style="list-style-type: none"> • Unique rib tread pattern • Special tread compound 	<ul style="list-style-type: none"> • Excellent road grip • High mileage

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
11.00-20	16	8.0	300	1105	19.5	3265@8.10	2865@7.40	518	20RR	TR 78A
11.00-22	16	8.0	295	1150	19.5	3524@8.15	3092@7.45	538	22RR	TR 78A

HEAVY DUTY TRUCK/BUS TYRES



MILER 2000



Features	Benefits
<ul style="list-style-type: none"> • Unique rib tread pattern • Extra strong casing 	<ul style="list-style-type: none"> • Excellent road grip and more retread • High mileage

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
12.00-20	18	8.5	315	1140	14.9	3725@8.10	3265@7.40	534	20RR	TR 78A

HIGHWAY



Features	Benefits
<ul style="list-style-type: none"> • Unique rib tread pattern • Extra strong casing 	<ul style="list-style-type: none"> • Excellent road grip and more retread • High mileage

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
9.00-20	10	7.0	260	1025	14.6	2095@5.60	1835@4.90	485	20N	TR 175A
10.00-20	12	7.5	278	1065	12.7	2470@6.00	2165@5.30	500	20NX	TR 78A
10.00-20	16	7.5	285	1070	12.5	3000@8.15	2630@7.4	504	20N	TR 78A
11-22.5	12	8.25	278	1054	15.2	2465@6.00	2160@5.30	504	-	Tubeless
11-22.5	16	8.25	278	1054	15.2	3005@8.10	2635@7.40	504	-	Tubeless
11-24.5	12	8.25	280	1115	15.2	2625@6.00	2305@5.30	522	-	Tubeless
11-24.5	16	8.25	280	1115	15.2	3195@8.10	2805@7.40	522	-	Tubeless
10.00-22	12	7.5	277	1105	15.2	2650@6.00	2300@5.30	521	22RR	TR 78A

HEAVY DUTY TRUCK/BUS TYRES



TOP MILER



Features	Benefits
<ul style="list-style-type: none"> • 5 rib design pattern • Unique fan like shoulder Design 	<ul style="list-style-type: none"> • Excellent road grip • Good mileage • Excellent traction

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
12.00-20	18	8.5	315	1135	14.5	3725@8.10	3265@7.40	525	20RR	TR 78A

TOP MILER 2000



Features	Benefits
<ul style="list-style-type: none"> • 5 rib design pattern • Unique fan like shoulder Design 	<ul style="list-style-type: none"> • Excellent road grip • Enhanced mileage • Excellent traction

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
12.00-20	18	8.5	320	1160	17.5	3725@8.10	3265@7.40	540	20RR	TR 78A



MULTI MILER 2000



Features	Benefits
<ul style="list-style-type: none"> • Unique tread compound • More larger voids • Special design with scoops at shoulder • Extra strong casing 	<ul style="list-style-type: none"> • Excellent mileage • Better road grip • More circulation of air and faster heat dissipation • Better safety and more retreads

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
11.00-20	16	8.0	295	1095	15.5	3265@8.10	2865@7.40	514	20RR	TR 78A



STEEL MUSCLE

Features	Benefits
<ul style="list-style-type: none"> • 4 rib design • Free rolling pattern • Premium tread compound • All wheel fitment 	<ul style="list-style-type: none"> • Avoids stone trapping • Enhanced mileage and traction • Better road grip

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
9.00 R 20	14	7.0	264	1020	14.0	2570@7.95	2255@7.25	478	20N	TR 175
10 R 22.5	14	7.5	250	1020	14.0	2570@7.95	2255@7.25	480	-	Tubeless



STEEL MUSCLE - L

Features	Benefits
<ul style="list-style-type: none"> • Long mileage • Aggressive pattern • Drive axle fitment 	<ul style="list-style-type: none"> • Even wear • Excellent traction

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
10.00 R 20	16	7.5	275	1060	18.5	3000@8.25	2630@7.6	493	20N	TR 78A
11.00 R 20	16	8	290	1085	18.5	3265@8.25	2865@7.6	505	20RR	TR 78A
11 R 22.5	16	8.25	275	1060	18.5	3000@8.25	2630@7.6	493	-	Tubeless



STEEL MUSCLE



Features	Benefits
<ul style="list-style-type: none"> • Free rolling pattern • Premium tread compound • All wheel fitment 	<ul style="list-style-type: none"> • Avoids stone trapping • Enhanced mileage and traction • Better road grip

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
10.00 R 20	16	7.5	275	1056	14.0	3000@8.25	2630@7.6	493	20N	TR 78A
11 R 22.5	16	8.25	275	1056	14.0	3000@8.25	2630@7.6	493	-	Tubeless
11 R 22.5	14	8.25	275	1056	14.0	2800@7.3	2650@7.3	493	-	Tubeless

STEEL MUSCLE



Features	Benefits
<ul style="list-style-type: none"> • Free rolling pattern • Premium tread compound • All wheel fitment 	<ul style="list-style-type: none"> • Avoids stone trapping • Enhanced mileage and traction • Better road grip

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
11.00 R 20	16	8	290	1085	16.5	3265@8.25	2865@7.6	505	20RR	TR 78A
12 R 22.5	16	9	288	1085	16.5	3265@8.25	2865@7.6	505	-	Tubeless



STEEL MUSCLE - C



Features	Benefits
<ul style="list-style-type: none"> • Specially designed tread block • Drive axle fitment 	<ul style="list-style-type: none"> • Cooler running • Excellent mileage • Superior traction & braking

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
11.00 R 20	16	8.0	295	1095	23.0	3265@8.25	2865@7.6	510	20RR	TR 78A

STEEL MUSCLE - S3B4



Features	Benefits
<ul style="list-style-type: none"> • Flat tread contour • Unique block design • Structural integrity • High Rubber Volume 	<ul style="list-style-type: none"> • Optimum Foot print to give • Even wear pattern • Optimize traction • Multiple retreading • Optimum mileage

TYRE SIZE	PLY	REC-RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	NON-SKID DEPTH	LOAD/INFLATION		STATIC LOADED	FLAP	TUBE VALVE
						SINGLE	DUAL			
10.00 R 20.0	16	7.5	276	1065	20.0	3000@8.5	2725@8.5	498	20N	TR78A
11.00 R 20.0	16	8.0	292	1092	20.0	3350@8.5	3075@8.5	509	20RR	TR78A
11.00 R 22.5	16	8.25	284	1066	19.8	3000@8.5	2725@8.5	498	-	Tubeless



STEEL MUSCLE



Features	Benefits
<ul style="list-style-type: none"> Highway service Specially designed tread 	<ul style="list-style-type: none"> Cooler running Excellent mileage

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
12.00 R 20	18	8.50	305	1125	15.0	3650@8.25	3250@7.6	520	20RR	TR 78A

STEEL MUSCLE - S1R4



Features	Benefits
<ul style="list-style-type: none"> Flat Tread Contour Longitudinal tread grooves Wear resistant tread compound Structural integrity Tread pattern with sipes and Edge treatment 	<ul style="list-style-type: none"> Optimum foot print to give Even wear pattern Good handling response Very high original milage Multiple retreading To avoid Erosion and Ompression wear

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
10 00R 20	16	7.5	277	1055	15.0	3000@8.5	2725@8.5	494	20N	TR 78A
11.00 R 20	16	8.0	293	1083	14.8	3350@8.5	3075@8.5	505	20RR	TR 78A
11 R 22.5	16	8.25	284	1057	14.5	3150@8.7	2900@8.7	496	-	Tubeless
295/80 R 22.5	16	9.0	292	1044	15.8	3550@8.8	3150@8.8	484	-	Tubeless



STEEL MUSCLE S7D4

Features	Benefits
<ul style="list-style-type: none"> • Unique cavity design • Tread Pattern with see through grooves • High Rubber Volume 	<ul style="list-style-type: none"> • Trailer tyre with even wear • Disperses water from tyre foot print • Optimum Mileage

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
11R 22.5	16	8.25	271	1043	11.3	3000@8.5	2725@8.5	489	-	Tubeless